WOLF OFFICIALTECH
5W-30 IL D1

25/09/2026
16185

Thanks to the low viscosity and excellent fluidity, this oil offers low wear, low emissions, and a strong fuel economy. Its carefully synthesized additive package targets soot and deposits to keep the engine clean. It is suitable for hybrid cars when the OEM specifications are met.

APPLICATIONS

This engine oil has been specifically developed to meet the challenging requirements of the latest GM Dexos1 Gen 3 specification and ILSAC GF-7 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

FEATURES

Cold start: high level of fluidity at low temperature
Fuel economy: great fuel economy and low exhaust emissions
Engine protection: ensures high level of the engine cleanliness

SPECIFICATIONS

API	approval SQ/RC
API	SN
API	SN Plus
API	SN/RC
API	SP
API	SP/RC
API	SQ
ILSAC	approval GF-7 A
ILSAC	GF-5
ILSAC	GF-6A
CHRYSLER	MS 13340
CHRYSLER	MS 6395
FIAT	9.55535-CR1
FORD	WSS-M2C945-A
FORD	WSS-M2C946-A
FORD	WSS-M2C946-B1
FORD	WSS-M2C947-A
FORD	WSS-M2C961-A1
GENESIS	SFU
GM	4718M
GM	6094M
GM	dexos™1 Gen 3
HONDA	SFU
HYUNDAI	SFU
INFINITI	SFU
JAGUAR	SFU
KIA	SFU
LAND ROVER	SFU
LEXUS	SFU
MITSUBISHI	SFU
SUZUKI	SFU
TATA	SFU
TOYOTA	SFU
VW	VWC 53034

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	63.4
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	11.0
Viscosity index	ASTM D2270		167
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	7.4
Pour point	ASTM D6892	°C	-39
Sulfated Ash	ASTM D874	Mass %	0.79
Flash Point COC	ASTM D92	°C	225

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com