WOLF CORS COMBI 10W30 LA

25/09/2026
3500

High performance formulation specifically developed for the lubrication of equipment used in construction, agriculture and public works machines. It offers considerable fuel saving and covers a wide set of applications such as engines, hydraulic systems, manual and powershift transmissions.

APPLICATIONS

Engine application: This oil is advised for the lubrication of heavy duty diesel engines and vehicles with and without particulate filter, it meets the requirements of the latest engine technologies with emission control systems Stage IIIB, Stage IV Final and Tier 4i, Tier 4 Final, as well as older generations (Stage I, II, IIIA, Tier 1, 2, 3). Gearboxes, powershift or manual, power take-off. Hydraulic systems of agricultural tractors and off-highway equipment.

FEATURES

Anti-wear and oxidation stability: reliable protection of critical parts
Cold start: high level of fluidity at low temperature

SPECIFICATIONS

ACEA	E9/E7/E5
API	CJ-4/CI-4 Plus/CI-4/CH-4
API	GL-4/SAE30
ISO	VG 46(After 100h)/HV
JASO	DH-1/DH-2
JCMA	HK 46W(extend.drain)
ALLISON	C4
CASE	MS1230
CATERPILLAR	ECF-3/ECF-2/ECF-1a
CATERPILLAR	HYDO ADVANCED 10/30
CATERPILLAR	TO-4 (SAE10W,30)
CUMMINS	CES 20081/78/77/76
DEUTZ	DQC-III-10/10LA
GLOBAL	DHD-1
KOMATSU	CLUTCH: TO-10,30
KOMATSU	HO-46 (HV)
MACK	EO-O Premium Plus
MAN	M3275-1/M3575
MTU	Oil Category 2 / 2.1
RENAULT	RLD-2/RLD-3
VOLVO	VDS-3/VDS-4
ZF	TE-ML 07D

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.860
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	74.5
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	11.8
Viscosity index	ASTM D2270		153
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	10.2
Pour point	ASTM D6892	°C	-39
CCS viscosity at -25°C	ASTM D5293	mPa.s	5800
Flash Point COC	ASTM D92	°C	224

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com