



1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

SAE 5W-30 DEX1 GEN2

VAICO No.:

V60-0390, V60-0393, V60-0394, V60-0395, V60-0396, V60-0397

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

High-performance low-friction engine oil, specially designed to minimise LSPI (Low Speed Pre-Ignition). New formulation prevents damage from knocking in direct injection engines with or without turbocharger. Not suitable for use in diesel engines.

3. PERFORMANCE DATA

3.1. Specifications:

API SN-RC • ILSAC GF-5

3.2. Fit to*:

Chrysler MS-6395

Ford WSS-M2C946-A

GM dexos1 Gen2, 95527874, 95599877, 95599919

Honda

Hyundai

Kia

Mazda

TYPICAL VALUES	METHOD	UNIT	VAICO SAE 5W-30 DEX1 GEN2
Density at 15°C	ASTM D4052	kg/m ³	845
Viscosity at 40°C	ASTM D445	mm ² /s	64,1
Viscosity at 100°C	ASTM D445	mm ² /s	11,3
Viscosity index (VI)	ASTM D2270	-	171
Pour point	ASTM D5950	°C	-45
COC flash point	ASTM D92	°C	224
Total base number	ASTM D2896	mg KOH/g	8,0
Sulphated ash	ASTM D874	Gew. %	0,94

* conforms to OEM specifications – The above values may vary within commercially accepted tolerances.