



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

hydraulic fluid
Article number: 64 92 4704
UFI: 6YD6-S22Y-A00N-7YXN

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Hydraulics oil

1.2.2 Uses advised against

For all uses not specified in SECTION 1.2.1

1.3 Details of the supplier of the safety data sheet

Company SWAG Autoteile GmbH
 Am Kiesberg 4-6
 42117 Wuppertal / GERMANY
 Phone +49 (0)202 26454-0
 Fax +49 (0)202 26454-5000
 Homepage www.swag.de
 E-mail info@swag.de

Address enquiries to

Technical information info@swag.de

Safety Data Sheet info@swag.de

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Skin Irrit. 2: H315 Causes skin irritation.
 Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms



Signal word

WARNING

Hazard statements

H315 Causes skin irritation.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P280 Wear protective gloves / protective clothing.
 P332+P313 If skin irritation occurs: Get medical advice / attention.
 P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Special labelling

Contains: reaction products of P-/N-/S-containing compounds with propionic acid, 3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid. EUH208 May produce an allergic reaction.



2.3 Other hazards

	none
Environmental hazards	Does not contain any PBT or vPvB substances. Contains no ingredients with endocrine-disrupting properties.
Other hazards	Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
30 - < 60	Distillates (petroleum), hydrotreated light naphthenic CAS: 64742-53-6, EINECS/ELINCS: 265-156-6, EU-INDEX: 649-466-00-2 GHS/CLP: Asp. Tox. 1: H304
15 - < 30	Distillates (petroleum), hydrotreated light paraffinic CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-XXXX GHS/CLP: Asp. Tox. 1: H304
15 - < 30	Distillates (petroleum), hydrotreated middle CAS: 64742-46-7, EINECS/ELINCS: 265-148-2, EU-INDEX: 649-221-00-X GHS/CLP: Acute Tox. 4: H332 - Asp. Tox. 1: H304 - Skin Irrit. 2: H315 - Aquatic Chronic 2: H411
5 - < 10	2-Propenoic acid,2-methyl-, dodecyl ester,polymer with eicosyl2-methyl-2-propenoate, hexadecyl2-methyl-2-propenoate, methyl2-methyl-2-propenoate, octadecyl2-methyl-2-propenoate, pentadecyl2-methyl-2-propenoate, tetradecyl and tridecyl2-methyl-2-propenoate GHS/CLP: Eye Irrit. 2: H319
2.5 - < 5	Base oil CAS: 72623-86-0, EINECS/ELINCS: 276-737-9, Reg-No.: 01-2119474878-16-XXXX GHS/CLP: Asp. Tox. 1: H304
< 0.5	2,6-di-tert-butylphenol CAS: 128-39-2, EINECS/ELINCS: 204-884-0, Reg-No.: 01-2119490822-33-XXXX GHS/CLP: Skin Irrit. 2: H315 - Aquatic Chronic 1: H410 - Aquatic Acute 1: H400, M-Factor (acute): 1, M-Factor (chronic): 1
0.1 - < 0.3	Reaction products of fatty acids, C16-18, C18 unsatd. with Amines, polyethylenepoly-, triethylenetetramine fraction and 3-(C9-C15, C12 rich, alk-1-enyl)dihydro-2,5-furandione EINECS/ELINCS: 947-263-6, Reg-No.: 01-2120761103-66-XXXX GHS/CLP: Repr. 2: H361 - Skin Irrit. 2: H315 - Aquatic Chronic 4: H413
< 0.25	reaction products of P-/N-/S-containing compounds with propionic acid EINECS/ELINCS: 939-700-4, Reg-No.: 01-2119982395-25 GHS/CLP: Skin Irrit. 2: H315 - Skin Sens. 1B: H317 - Aquatic Acute 1: H400 - Aquatic Chronic 2: H411
< 0.25	3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid CAS: 268567-32-4, EINECS/ELINCS: 434-070-2, Reg-No.: 01-2119658068-31 GHS/CLP: Eye Dam. 1: H318 - Skin Sens. 1B: H317 - Aquatic Chronic 3: H412

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements: see SECTION 16.



SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Take off contaminated clothing and wash before reuse.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.
Skin contact	When in contact with the skin, clean with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Seek medical advice immediately. Do not induce vomiting. Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
If swallowed or in the event of vomiting, risk of product entering the lungs.
Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Foam, dry powder, water spray jet, carbon dioxide.
Extinguishing media that must not be used	Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)
Sulphur oxides (SO_x).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).
Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.

Fire class (DIN EN 2): B

Do not smoke.

Do not eat, drink or smoke when using this product.

Wash hands before breaks and after work.

Cloths contaminated with product should not be kept in trouser pockets.

Use barrier skin cream.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Do not store together with food and animal food/diet.

Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
Distillates (petroleum), hydrotreated light paraffinic
CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-XXXX
Long-term exposure: 5 mg/m ³ , ACGIH TLV (OIL MIST)

DNEL

Substance
2,6-di-tert-butylphenol, CAS: 128-39-2
Industrial, inhalative, Long-term - systemic effects, 70.61 mg/m ³
Industrial, dermal, Long-term - systemic effects, 11.25 mg/kg bw/day
general population, inhalative, Long-term - systemic effects, 20.9 mg/m ³
general population, oral, Long-term - systemic effects, 6.75 mg/kg bw/day
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
Industrial, dermal, Long-term - systemic effects, 1.25 mg/kg bw/d (AF=100)
Industrial, inhalative, Long-term - systemic effects, 4.4 mg/m ³ (AF=25)
general population, inhalative, Long-term - systemic effects, 1.1 mg/m ³ (AF=50)
general population, dermal, Long-term - systemic effects, 0.6 mg/kg bw/d (AF=200)
general population, oral, Long-term - systemic effects, 0.6 mg/kg bw/d (AF=200)
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
Industrial, dermal, Long-term - systemic effects, 0.97 mg/kg bw/day
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5.58 mg/m ³
general population, oral, Long-term - systemic effects, 0.74 mg/kg bw/day
reaction products of P-/N-/S-containing compounds with propionic acid, CAS: 94270-86-7
Industrial, inhalative, Long-term - systemic effects, 1.3 mg/m ³ (AF=30)
Industrial, dermal, Long-term - systemic effects, 0.4 mg/kg bw/d (AF=120)
general population, dermal, Long-term - systemic effects, 0.2 mg/kg bw/d (AF=240)
general population, inhalative, Long-term - systemic effects, 0.3 mg/m ³ (AF=60)
Reaction products of fatty acids, C16-18, C18 unsatd. with Amines, polyethylenepoly-, triethylenetetramine fraction and 3-(C9-C15, C12 rich, alk-1-enyl)dihydro-2,5-furandione
Industrial, inhalative, Long-term - systemic effects, 3.72 mg/m ³ (AF= 18)
Industrial, dermal, Long-term - systemic effects, 1.04 mg/kg bw/d (AF= 72)
general population, oral, Long-term - systemic effects, 0.625 mg/kg bw/d (AF= 120)
general population, dermal, Long-term - systemic effects, 0.625 mg/kg bw/d (AF= 120)
general population, inhalative, Long-term - systemic effects, 1.1 mg/m ³ (AF= 30)

PNEC

Substance
2,6-di-tert-butylphenol, CAS: 128-39-2
soil, 697 µg/kg soil dw
freshwater, 700 ng/L
seawater, 70 ng/L
sewage treatment plants (STP), 10 mg/L
sediment (seawater), 31.7 µg/kg sediment dw

oral (food), 60 mg/kg food
sediment (freshwater), 317 µg/kg sediment dw
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
seawater, 0.007 mg/L (AF=500)
sewage treatment plants (STP), 10 mg/l (AF=10)
sediment (freshwater), 23 mg/kg dw
freshwater, 0.072 mg/L (AF=50)
sediment (seawater), 2.3 mg/kg dw
soil, 4.54 mg/kg dw
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
oral (food), 9.33 mg/kg food
reaction products of P-/N-/S-containing compounds with propionic acid, CAS: 94270-86-7
seawater, 0 mg/l (AF=10.000)
freshwater, 0.001 mg/l (AF=1000)
sewage treatment plants (STP), 0.69 mg/l (AF=100)
Reaction products of fatty acids, C16-18, C18 unsatd. with Amines, polyethylenepoly-, triethylenetetramine fraction and 3-(C9-C15, C12 rich, alk-1-enyl)dihydro-2,5-furandione
sediment (freshwater), 3 772.830 g/kg dw
sediment (seawater), 377.28 g/kg dw
sewage treatment plants (STP), 100 mg/L (AF= 10)
freshwater, 0.496 mg/L (AF= 1000)
seawater, 0.05 mg/L (AF= 10 000)
soil, 3 935.35 g/kg dw

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances. General exposure limit for oil mist should be noted.
Eye protection	If there is a risk of splashing: Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0.11 mm: Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	Light protective clothing.
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	Breathing apparatus in the event of aerosol or mist formation. Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	See SECTION 6+7.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	liquid
Color	green-yellow
Odor	characteristic
Odour threshold	not determined
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	No information available.
Flash point [°C]	126 (ISO 2592)
Flammability (solid, gas) [°C]	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	< 0.01 (20°C)
Density [g/cm ³]	ca. 0.867 (DIN 51757) (15 °C / 59,0 °F)
Relative density	not determined
Bulk density [kg/m ³]	not applicable
Solubility in water	immiscible
Solubility other solvents	No information available.
Partition coefficient [n-octanol/water]	not determined
Kinematic viscosity	ca. 21 mm ² /s (40°C) (DIN 51562/T1) 6.3 mm ² /s (100°C)
Relative vapour density	not determined
Evaporation speed	not determined
Melting point [°C]	ca. -51 (ISO 3016)
Auto-ignition temperature [°C]	not determined
Decomposition temperature [°C]	> 300
Particle characteristics	No information available.

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating, because the thermal decomposition starts from > 300°C.



10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

No hazardous decomposition products known.



SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Product
oral, Based on the available information, the classification criteria are not fulfilled.
Substance
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
LD50, oral, Rat, > 5000 mg/kg
2,6-di-tert-butylphenol, CAS: 128-39-2
LD50, oral, Rat, 5000 mg/kg bw
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
LD50, oral, Rat, > 2000 mg/kg bw
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
LD50, oral, Rat, 5000 mg/kg bw
Base oil, CAS: 72623-86-0
LD50, oral, Rat, > 2001 mg/kg
reaction products of P-/N-/S-containing compounds with propionic acid, CAS: 94270-86-7
LD50, oral, Rat, 3313 mg/kg bw
Reaction products of fatty acids, C16-18, C18 unsatd. with Amines, polyethylenepoly-, triethylenetetramine fraction and 3-(C9-C15, C12 rich, alk-1-enyl)dihydro-2,5-furandione
LD50, oral, Rat (female), > 2000 mg/kg bw, OECD 423
NOAEL, oral, Rat, 75 mg/kg bw/day

Acute dermal toxicity

Product
dermal, Based on the available information, the classification criteria are not fulfilled.
Substance
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
LD50, dermal, Rabbit, > 2000 mg/kg
2,6-di-tert-butylphenol, CAS: 128-39-2
LD0, dermal, Rat, 1000 - 33000 mg/kg bw
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
LD50, dermal, Rat, > 2000 mg/kg bw
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw
Base oil, CAS: 72623-86-0
LD50, dermal, Rabbit, > 2001 mg/kg
reaction products of P-/N-/S-containing compounds with propionic acid, CAS: 94270-86-7
LD50, dermal, > 2000 mg/kg bw

Acute inhalational toxicity

Product
inhalative, Based on the available information, the classification criteria are not fulfilled.
Substance



Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

LC50, inhalative, Rat, 5000 mg/m ³ /4h

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Base oil, CAS: 72623-86-0

LC50, inhalative, Rat, > 5.53 mg/l/4h

Serious eye damage/irritation Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

Eye, non-irritating

Skin corrosion/irritation Toxicological data of complete product are not available.
Irritant
Calculation method

Substance

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

dermal, non-irritating

Respiratory or skin sensitisation Toxicological data of complete product are not available.
May produce an allergic reaction.
Calculation method

Substance

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

dermal, non-sensitizing

Specific target organ toxicity — single exposure Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — repeated exposure Based on the available information, the classification criteria are not fulfilled.

Substance

2,6-di-tert-butylphenol, CAS: 128-39-2
--

NOAEL, oral, Rat, 100 mg/kg bw/day, OECD 407, negativ

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

NOAEC, inhalative, Rat, 980 mg/m ³ (subacute), no adverse effect observed
--

LOAEL, dermal, mouse, 100 mg/kg bw/day (chronic), The effects observed are not sufficient for classification.

LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.

Mutagenicity Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

in vitro, negativ

Reproduction toxicity Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

2,6-di-tert-butylphenol, CAS: 128-39-2
--

NOAEL, oral, Rat, 150 mg/kg bw/day, OECD 414, negativ, Effect on developmental toxicity,
--



NOAEL, oral, Rat, 150 mg/kg bw/day, OECD 421, negativ, Effect on fertility,
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed

- Development

Substance
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed
2,6-di-tert-butylphenol, CAS: 128-39-2
NOAEL, oral, Rat, 150 mg/kg bw/day, OECD 414, negativ, Effect on developmental toxicity,
NOAEL, oral, Rat, 150 mg/kg bw/day, OECD 421, negativ, Effect on fertility,

Carcinogenicity

Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard

Based on the available information, the classification criteria are not fulfilled.

General remarks

Toxicological data of complete product are not available.
The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

11.2 Information on other hazards

Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

Other information

none



SECTION 12: Ecological information

12.1 Toxicity

Substance
2,6-di-tert-butylphenol, CAS: 128-39-2
LC50, (14d), fish, 1 mg/L
LC50, (4d), fish, 1.4 mg/L
LC50, (21d), Invertebrates, 230 µg/L
EC50, (24h), Invertebrates, 590 µg/L
EC50, (24h), Algae, 1.7 - 2.3 mg/L
EC50, (48h), Algae, 1.7 - 3.5 mg/L
EC50, (72h), Algae, 1.4 - 3.6 mg/L
EC50, (4d), Algae, 1.2 - 3.9 mg/L
EC50, (21d), Invertebrates, 140 µg/L
EC50, (48h), Invertebrates, 450 µg/L
LC0, (48h), Invertebrates, 76 µg/L
NOEC, (21d), Invertebrates, 35 µg/L
NOEC, (14d), fish, 300 µg/L
NOEC, (96h), Algae, 640 - 2100 µg/L
LOEC, (21d), Invertebrates, 86 µg/L
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
LC50, (96h), fish, 54 mg/l
EC50, (48h), Daphnia magna, 53 mg/l
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
NOELR, (14d), fish, 1 g/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), fish, 100 mg/L
reaction products of P-/N-/S-containing compounds with propionic acid, CAS: 94270-86-7
LC50, (96h), 1 - 10 mg/l
EC50, (48h), Daphnia magna, 1 - 10 mg/l
Reaction products of fatty acids, C16-18, C18 unsatd. with Amines, polyethylenepoly-, triethylenetetramine fraction and 3-(C9-C15, C12 rich, alk-1-enyl)dihydro-2,5-furandione
LC50, (96h), fish, 1000 mg/L
EC50, (72h), Algae, 370 - 496 mg/L
EC50, (48h), Invertebrates, 1000 mg/L

12.2 Persistence and degradability

Behaviour in environment compartments

Behaviour in sewage plant not determined

Biological degradability not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.



12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the disposal contractor/authorities if necessary.
Disposal in an incineration plant in accordance with the regulations of the local authorities.
In according to RoHS!

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

**14.3 Transport hazard class(es)**

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

EEC-REGULATIONS 2008/98/EC 2000/532/EC; 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2023)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.

- **Observe employment restrictions for people** Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.

- **VOC (2010/75/CE)** 0%



15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H361 Suspected of damaging fertility or the unborn child.
 H413 May cause long lasting harmful effects to aquatic life.
 H412 Harmful to aquatic life with long lasting effects.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.
 H315 Causes skin irritation.
 H332 Harmful if inhaled.
 H304 May be fatal if swallowed and enters airways.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 ATE = acute toxicity estimate
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging
 DMEL = Derived Minimum Effect Level
 DNEL = Derived No Effect Level
 EC50 = Median effective concentration
 ECB = European Chemicals Bureau
 EEC = European Economic Community
 EINECS = European Inventory of Existing Commercial Chemical Substances
 EL50 = Median effective loading
 ELINCS = European List of Notified Chemical Substances
 EmS = Emergency Schedules
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IC50 = Inhibition concentration, 50%
 IMDG = International Maritime Code for Dangerous Goods
 IUCLID = International Uniform Chemical Information Database
 IVIS = In vitro irritation score
 LC50 = Lethal concentration, 50%
 LD50 = Median lethal dose
 LC0 = lethal concentration, 0%
 LOAEL = lowest-observed-adverse-effect level
 LL50 = Median lethal loading
 LQ = Limited Quantities
 MARPOL = International Convention for the Prevention of Marine Pollution from Ships
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 PBT = Persistent, Bioaccumulative and Toxic substance
 PNEC = Predicted No-Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
 STP = Sewage Treatment Plant
 TLV@/TWA = Threshold limit value – time-weighted average
 TLV@STEL = Threshold limit value – short-time exposure limit
 VOC = Volatile Organic Compounds
 vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Skin Irrit. 2: H315 Causes skin irritation. (Calculation method)
 Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)



Modified position

SECTION 11 been added: Contains no ingredients with endocrine-disrupting properties.

SECTION 12 been added: Contains no ingredients with endocrine-disrupting properties.