WOLF ELECTRUM COOLANT

25/09/2026
65340

This premium "lobrid" MEG based battery coolant combines the Organic Additive Technology with mineral (silicate) corrosion inhibitors.

APPLICATIONS

This Si-OAT battery coolant is especially developed for the protection of electric and modern combustion engines cooling systems made of aluminium and aluminium alloys.

FEATURES

Anti-freeze properties: high level of cold temperature performance
Anti-corrosion properties: high level of corrosion protection
System protection: high level of heat transfer and dispersion

SPECIFICATIONS

ASTM	D3306	SAE	J1034
ASTM	D4985	TESLA	SFU
ASTM	D6210		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 20°C	ASTM D4052	g/ml	1.069
Colour	VISUAL		VIOLET
Freezing point	ASTM D1177	°C	-36
ELECTRIC CONDUCTIVITY (25°C)	ASTM D1125	µS/cm	2300

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV