

WOLF RACING TRANS/AXLE LS 75W-90 ESTER

02/12/2025
65522

This is a sustainable RRBO high performance gearbox and transaxle lubricant, enriched with ester and PAO, for racing vehicles offering an excellent anti-wear and EP protection, a better resistance at high temperatures and a longer oil life time.

APPLICATIONS

This sustainable RRBO lubricant can be used in gearboxes, transaxles and differentials with or without limited slip of racing vehicles.

FEATURES

Anti-wear protection: extended component life.
Extended oil life: excellent thermal and oxidation stability.

SPECIFICATIONS

API	GL-5	MACK	GO-J
API	MT-1	MB	235.61
MIL	L-2105 B	MCLAREN	MOB PTX
MIL	L-2105 C	M-SPORT	Rally3/Rally4/Rally5/R1/R2/R3
MIL	L-2105 D	NISSAN	2189E
MIL	L-2105 E	PORSCHE	999.917.067.00
SAE	J 2360	PORSCHE	999.917.090.00
ARVIN MERITOR	0-76-E	RICARDO	SFU
BMW	83 22 1 470 080	SADEV	SFU
BMW	83 22 2 282 583	SALISBURY	SFU
BMW	MSP/A	SCHMIDT	SFU
CHRYSLER	MS 9763	ANTRIEBSTECHNIK	
DANA	SFU	VW	G 052 539
DREXLER	SFU	VW	G 055 145
FERRARI	PAKELO GLOBAL MULTIGEAR DLS	X-TRAC	SFU
FORD	ESW-M2C104-A	ZF	TE-ML 05A
FORD	ESW-M2C119-A	ZF	TE-ML 05B
FORD	WSP-M2C197-A	ZF	TE-ML 05C
FORD	WSS-M2C942-A	ZF	TE-ML 05D
GM	1940058	ZF	TE-ML 07A
GM	88862624	ZF	TE-ML 12D
GM	88862625	ZF	TE-ML 12N
GM	93165388	ZF	TE-ML 16F
GM	9986226	ZF	TE-ML 16G
GM	9986290	ZF	TE-ML 19C
HEWLAND	SFU	ZF	TE-ML 21A
HOLLINGER	SFU	ZF	TE-ML 21C

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.872
Kinematic viscosity at 40°C	ASTM D445	mm²/s	99.3
Kinematic viscosity at 100°C	ASTM D445	mm²/s	15.1
Viscosity index	ASTM D2270		160
Pour point	ASTM D6892	°C	-51
Colour	VISUAL		LIGHT BROWN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

