

WOLF VITALTECH

75W90 GL 5

22/08/2023
2305

This is a full synthetic lubricant based on carefully selected very high quality base oils, which can be used in a wide field of applications. Because of its special composition, it is particularly suited for synchronized gear boxes, as well as heavily loaded differentials.

APPLICATIONS

This oil is recommended for all components of mechanical transmissions (gear boxes, transfer boxes, differentials, etc.) of trucks and four-wheel drive vehicles.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear and oxidation stability: superior protection of critical parts
Extended oil life: excellent thermal and oxidation stability

PERFORMANCE

API	GL-4	MB	235.11
API	GL-5	MB	235.8
API	MT-1	RENAULT	B0032/3 Annex 3
MIL	PRF-2105E	SCANIA	STO 1:0
SAE	J 2360	VOLVO	97312
ARVIN MERITOR	0-76-N	ZF	TE-ML 02B
BMW	OSP	ZF	TE-ML 05B
CHRYSLER	MS 9763	ZF	TE-ML 07A
DAF	GL5/MIL-PRF-2105E	ZF	TE-ML 08
DAIMLER TRUCK	DTFR 12B140	ZF	TE-ML 12B
DAIMLER TRUCK	DTFR 13B110	ZF	TE-ML 12L
IVECO	MIL-PRF-2105E	ZF	TE-ML 12N
MACK	GO-J	ZF	TE-ML 16F
MAN	341 E-3	ZF	TE-ML 17B
MAN	341 Z-2	ZF	TE-ML 19C
MAN	342 M-3	ZF	TE-ML 21B

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.862
Kinematic viscosity at 40°C	ASTM D445	mm²/s	70.2
Kinematic viscosity at 100°C	ASTM D445	mm²/s	15.0
Viscosity index	ASTM D2270		226
Pour point	ASTM D6892	°C	-42
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	80000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

