

0W-20 C5 Pro S

Description:

0W-20 C5 Pro S is a fully synthetic low friction oil to be used in gasoline and diesel engines for passenger cars. The special formulation assures maximum thermal and mechanical stability, excellent viscosity temperature dependency and low evaporation loss. The low friction properties of the used synthetic base stocks provide in conjunction with the most modern antifriction additives noticeable reduction of fuel consumption and thus for protection of environment by decreasing pollution.

Properties:

0W-20 C5 Pro S grants maximum wear protection and features best low temperature properties. These assure fast oil provision at all lubrication areas and minimize cold starting wear. Highly effective dispersant additives prevent sludge built-up in the oil circuit and deposits on piston and inlets valves. The compatibility with elastomers, used in engines, is assured.

Specification / Recommendations:

ACEA C5/C6	VW-Norm 508 00 und VW-Norm 509 00
API SP / SP RC	VW TL 52577
FORD WSS-M2C956-A1	Porsche C20
ILSAC GF-6A	

The product is not backwards compatible with VW 504 00 / 507 00 or other VW specifications.

Typical Values:

0W-20 C5 Pro S	Unit	Value	Method
Density at 15°C	kg/m ³	843	DIN 51 757
Viscosity at 100°C	mm ² /s	8,1	DIN 51 562
Viscosity at - 35°C (CCS)	mm ² /s	5630	DIN 51 562
Pourpoint	°C	-54	DIN ISO 3016
Flashpoint	°C	234	DIN ISO 2592
TBN	mg KOH/g	8,6	DIN ISO 3771

Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded. Further information is available on the MSDS.

Hengst SE

Nienkamp 55-85
48147 Münster
Germany
Tel.: +49 251 20202-0

