

# CHAMPION **ECO FLOW** 10W30 SP/RC G6 HC

This semi-synthetic oil significantly reduces wear and ensures fuel savings and lower CO2 emissions. Optimized additive package reduces soot and deposits and keeps the engine clean.

## APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest ILSAC GF-6 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

## FEATURES

Total engine protection: performance in keeping the engine clean.

Fuel economy: superior fuel economy and CO2 reduction.

Cold start: excellent fluidity at low temperature.

## SPECIFICATIONS

API	approval SN Plus	ILSAC	approval GF-6 A
API	approval SP/RC	ILSAC	GF-5
API	SN/RC	CHRYSLER	MS 6395
API	SP	GM	6094M

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	64.2
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	10.6
Viscosity index	ASTM D2270		155
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	7.4
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

