WOLF ECOTECH 0W30 C3 FE

06/10/2026
16105

This is a full synthetic lubricant based on carefully selected very high quality base oils. It is a "low saps", low viscosity engine oil of the latest generation, for the lubrication of gasoline and diesel engines. Significant fuel economy can be obtained, compaired to standard motor oils.

APPLICATIONS

This product is aimed and specially formulated for usage in diesel and gasoline engines of BMW group passenger vehicles. It can also be used in other OEM diesel and gasoline engines where there is a need for a 0W30 grade low SAPS oil.

FEATURES

Engine protection: ensures high level of the engine cleanliness
Fuel economy: the purpose is good fuel economy and low exhaust emissions
Cold start: high level of fluidity at low temperature

SPECIFICATIONS

ACEA	C2	MB	229.31
ACEA	C3	MB	229.51
API	SN/CF	MB	229.52
BMW	LONGLIFE-04	RENAULT	RN 0700
FIAT	9.55535-DS1	RENAULT	RN 0710
FIAT	9.55535-GS1		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.842
Kinematic viscosity at 40°C	ASTM D445	mm²/s	66.6
Kinematic viscosity at 100°C	ASTM D445	mm²/s	12.1
Viscosity index	ASTM D2270		182
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	7.8
Pour point	ASTM D6892	°C	-45
Sulfated Ash	ASTM D874	Mass %	0.8
Flash Point COC	ASTM D92	°C	224
CCS viscosity at -35°C	ASTM D5293	mPa.s	5900

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV