WOLF EXTENDTECH 85W140 GL 5

25/09/2026
2309

This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

APPLICATIONS

Recommended for all hypoid transmissions and also suitable for spiral bevel gears, worm wheels and most transaxles.

FEATURES

Frictional properties: easy gear shifting
Anti-wear protection: long transmission life

SPECIFICATIONS

API	GL-4	NH	NH 524A
API	GL-5	SCANIA	STO 1:0
API	MT-1	VOLVO	97310
FERMEC	SFU	ZF	TE-ML 05A
MIL	L-2105 C	ZF	TE-ML 07A
MIL	L-2105 D	ZF	TE-ML 08
MIL	L-2105 E	ZF	TE-ML 12E
AGCO/ALLIS	GEAR/AXLE OIL 775	ZF	TE-ML 16B
CASE	MS1316	ZF	TE-ML 16C
FIAT-ALLIS	SFU	ZF	TE-ML 16D
HYUNDAI	SFU	ZF	TE-ML 17B
MACK	GO-J	ZF	TE-ML 19B
MAN	342 M-1	ZF	TE-ML 21A
MB	235.0		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.908
Kinematic viscosity at 40°C	ASTM D445	mm²/s	367
Kinematic viscosity at 100°C	ASTM D445	mm²/s	26.1
Viscosity index	ASTM D2270		95
Pour point	ASTM D6892	°C	-15
Copper corrosion (150°C, 3h)	ASTM D130		1B
Flash Point COC	ASTM D92	°C	215

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV