

MQP 15W-40 HD Mixed

1 LITRE	5 LITRE	25 LITRE	BULK
VOL106	VOL108	VOL151	VOL703

PRODUCT SPECIFICATION

Description

High performance, versatile engine oil for use in passenger and light commercial diesel and petrol engines across a range of applications including moderately extended drain periods.

MQP 15W-40 HD Mixed is a mixed fleet lubricant, incorporating high quality minerals, oils and performance additives, suitable high performance, versatile mixed fleet engine oil, formulated to offer improved lubrication and longevity for passenger and light commercial vehicles. MQP is designed to achieve improved performance, efficiency levels and engine cleanliness whilst ensuring critical components are protected from wear under extreme conditions, including extended oil drain periods. MQP 15W-40 HD Mixed may also be used in transmissions, hydraulic systems, PTOs, compressors, etc. where a product of this type and specification is required.

- Extended drain period support
- Improved engine cleanliness
- Improved protection from engine wear, rust and corrosion
- Anti-sludge control

Performance Levels

Allison C4
 API CG-4 / CF / SL / SJ
 MACK EO-L
 MAN 271
 MB 229.1 / 228.1
 Volvo VDS2
 VW 505.00
 BR 669 (Multigrade Crankcase
 Oil 15W-40)

Physical Characteristics	
Viscosity at 100°C, cSt.	14.3
Viscosity @ 40°C, cSt.	102.1
Viscosity Index	145
TBN, mg/KOH/g	9.8
Flash Point (Closed), °C	205
Density at 15.6°C	0.880
Pour Point, °C	-35
Appearance	Amber liquid
CCS @ -20°C (mPas)	7000 max
Sulphated Ash (%Wt)	1.3

Figures based on average production values.

TDS Oil MQP 15W-40 HD Mixed - 16.08.19 Issue 17

