WOLF OFFICIALTECH
ATF LIFE PROTECT 8

25/09/2026
3016

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

APPLICATIONS

Exclusively intended for the ZF 6,8 and 9 speed automatic transmissions, as fitted in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT group.

FEATURES

Anti-wear protection: long transmission life
Frictional properties: very smooth gear shifting, no vibration
Oil life durability: high level of thermal and oxidation stability

SPECIFICATIONS

ACURA	08200-9016A	JAGUAR	02JDE26444
ACURA	ATF TYPE 3.0	LAND ROVER	LR023288
ATF	L 12108	LAND ROVER	LR023289
BMW	83 22 2 289 720	MB	236.82
BMW	83 22 2 305 397	MOPAR	68157995AB
BMW	83222152426	MOPAR	68218925AA
BMW	83225A12A00	NISSAN	MATIC-R
BMW	ATF3+	VW	G 055 162
CHRYSLER	68157995AA	VW	G 060 162
FIAT	9.55550-AV5	ZF	S671 090 312
HONDA	08200-9017	ZF	TE-ML 11
HONDA	ATF TYPE 3.1		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm²/s	31.9
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.32
Viscosity index	ASTM D2270		153
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV