WOLF ECOTECH 75W PREMIUM

25/09/2026
2218

This is a full synthetic lubricant based on carefully selected very high quality base oils with low viscosity, used in manual gearboxes of passenger cars, which allows to achieve the highest fuel economy. It offers optimized cold start properties and stable viscosity/temperature behavior.

APPLICATIONS

This product is specifically formulated for a large variety of OEM gearboxes for which low viscosity manual transmission fluids are recommended.

FEATURES

Anti-wear protection: long transmission life
Oil life durability: high level of thermal and oxidation stability
Frictional properties: very smooth gear shifting, no vibration

SPECIFICATIONS

API	GL-4 +	FORD	WSS-M2C200-D3
BMW	23 00 7 533 513	FORD	WSS-M2C200-E1
BMW	23 00 7 533 819	GM	1052931
BMW	23001434404	GM	12345349
BMW	23007533513/818	GM	12345577
BMW	81 22 2 339 384	GM	12377916
BMW	83 22 0 309 031	GM	1940004
BMW	83 22 0 397 244	GM	1940774
BMW	83 22 2 339 219	GM	9985535
BMW	83 22 2 339 221	GM	9985648
BMW	83 22 5 A53 CB2	GM	9986105
BMW	83 22 7 533 818	GM	MTF BOT 0063
BMW	83220396706	JAGUAR-LAND ROVER	STJLR GX73-M1R564-AA
BMW	83222167666	MB	235.10
BMW	83227533818	MB	235.17
BMW	MTF LT-1	MB	235.71
BMW	MTF LT-2	MB	235.73
BMW	MTF LT-3	MB	A 002 989 04 03
BMW	MTF LT-5	NISSAN	32001 1BY0A
CHRYSLER	4874464	NISSAN	LV MT-1
CHRYSLER	4874465	PSA	9730 A8
CHRYSLER	MS 90031-H1	PSA	B71 2316
CHRYSLER	MS 9224	PSA	B71 2317
CHRYSLER	MS 9417	TOYOTA	08885-81001
FIAT	9.55550-MZ14	TOYOTA	08885-81081
FIAT	9.55550-MZ2	VOLVO	1161838
FIAT	9.55550-SA1	VOLVO	1161839
FORD	WSD-M2C200-D	VOLVO	31280771
FORD	WSS-M2C200-D1	VW	G 009 317
FORD	WSS-M2C200-D2	VW	G 052 171

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

VW	G 052 178	VW	G 055 512
VW	G 052 512	VW	G 055 532
VW	G 052 527	VW	G 055 726
VW	G 052 549	VW	G 060 726
VW	G 052 726	VW	G 070 726
VW	G 052 798	VW	N 05279800

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	29.93
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	6.31
Viscosity index	ASTM D2270		169
Pour point	ASTM D6892	°C	-42
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	13800
Flash Point COC	ASTM D92	°C	210

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com