

ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 9

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

 Trade name:
 ZF-LIFEGUARDFLUID 9

 Product code:
 AA01-500.001

1.2 Relevant identified uses of the substance or mixture and uses advised against

Transmission oil.

Use of the Substance/Mixture:

Uses advised against:

This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

ZF Friedrichshafen AG ZF Aftermarket Obere Weiden 12 97424 Schweinfurt Germany +49 9721 475 60 www.zf.com/contact

1.4 Emergency telephone number

24/7h Emergency telephone number: +49 (0)89 19240 Information in German and English

2. Hazards identification

2.1 GHS Classification

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS Based on available data this substance / mixture does not meet the classification criteria.

2.2 GHS label elements

Labelling

Hazard pictograms:

No Hazard Symbol required

Signal word:

No signal word

© ZF Friedrichshafen AG

Trade name: ZF-LIFEGUARDFLUID 9

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



ZF Aftermarket

Hazard statements	
PHYSICAL HAZARDS:	Not classified as a physical hazard under GHS criteria.
HEALTH HAZARDS:	Not classified as a health hazard under GHS criteria.
ENVIRONMENTAL HAZARDS:	Not classified as environmental hazard according to GHS criteria.
Precautionary statements: Prevention:	No precautionary phrases.
Response:	No precautionary phrases.
Storage:	No precautionary phrases.
Disposal:	No precautionary phrases.

2.3 Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria. Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

3. Composition/information on ingredients

3.2 Mixtures

Chemical nature

Synthetic base oil and additives. Highly refined mineral oil. The highly refined mineral oil contains <3% (w/w) DMSO extract, according to IP346.

* contains one or more of the following CAS-numbers: 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9.



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 9

Hazardous components

Chemical name	CAS-No.	Classification	Concentration [%]
Alkyl acetamid	866259-61-2	Skin Sens.1B; H317	1 - 3
Calcium sulphonate	75975-85-8	Skin Sens.1B; H317	0,1 - 0,9
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox. 1; H304	0 - 90

For explanation of abbreviations see section 16.

4. First aid measures

4.1	Description of first aid measures General advice:	Not expected to be a health hazard when used under normal conditions.
	Protection of first-aiders:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
	lf inhaled:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
	In case of skin contact:	Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
	In case of eye contact:	Flush eye with copious quantities of water. If persistent irritation occurs, obtain medi- cal attention.
	If swallowed:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
	Protection of first-aiders:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

© ZF Friedrichshafen AG

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



Trade name: ZF-LIFEGUARDFLUID 9

ZF Aftermarket

4.2 Most important symptoms and effects, both acute and delayed

Symptoms:

Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment:	Notes to doctor/physician:
	Treat symptomatically.

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media:	Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting:	Hazardous combustion products may in- clude: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
---------------------------------------	---

5.3 Advice for firefighters

Specific extinguishing methods:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for fire- fighters:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is ex- pected. Self-Contained Breathing Appa- ratus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



Trade name: ZF-LIFEGUARDFLUID 9

(e.g. Europe: EN469).

Specific extinguishing methods:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Hazchem Code:	None

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions:	For non emergency personnel: Avoid contact with skin and eyes.
Emergency responders:	For emergency responders: Avoid contact with skin and eyes.

6.2 Environmental precautions

Environmental precautions:	Use appropriate containment to avoid envi- ronmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appro- priate barriers. Local authorities should be advised if sig- nificant spillages cannot be contained.

6.3 Methods and materials for containment and cleaning up

Slippery when spilt. Avoid accidents, clean up immediately.

Prevent from spreading by making a barrier with sand, earth or other containment material.

Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly

6.4 Reference to other sections

Methods for cleaning up:

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

SAFETY DATA SHEET According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Trade name: ZF-LIFEGUARDFLUID 9



7.	Handling and storage	
	General Precautions:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circum- stances to help determine appropriate con- trols for safe handling, storage and dispos- al of this material.
7.1	Precautions for safe handling	
	Advice on safe handling:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper han- dling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
	Product Transfer:	This material has the potential to be a stat- ic accumulator. Proper grounding and bonding procedures should be used during all bulk transfer op- erations.
	Avoidance of contact:	Strong oxidising agents
7.2	Conditions for safe storage, including	g any incompatibilities

Other data:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable contain- ers. Store at ambient temperature.
Packaging material:	Suitable material: For containers or con- tainer linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice:	Polyethylene containers should not be ex- posed to high temperatures because of possible risk of distortion.

© ZF Friedrichshafen AG

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



Trade name: ZF-LIFEGUARDFLUID 9

8. Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of expo- sure)	Control para- meters / Per- missible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m³	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (inhalable fraction)	5 mg/m³	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls Engineering measures

The level of protection and types of controls necessary will vary depending

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



7F Aftermarket

Trade name: ZF-LIFEGUARDFLUID 9

upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping

Personal protective equipment Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection:

Hand protection:

If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.



Trade name: ZF-LIFEGUARDFLUID 9

	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appro- priate maintenance and replacement re- gimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
Skin and body protection:	Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical re- sistant gloves.
Respiratory protection:	No respiratory protection is ordinarily re- quired under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meet- ing relevant legislation. Check with respira- tory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].

Thermal hazards:

Not applicable

Environmental exposure controls



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 9

General advice: Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Liquid at room temperatur
Colour:	Blue
Odour:	Slight hydrocarbon
Odour Threshold:	Data not available
pH:	Not applicable

Pour point	-42° C / -44° F	DIN ISO 3016
Melting / freezing point	Data not available	
Initial boiling point and boiling range	> 280° C / 536° F	estimated value(s)
Flash point	>= 185 °C / >= 365 °F	ISO 2592
Evaporation rate	Data not available	
Flammability (solid, gas)	Data not available	
Upper explosion limit	Typical 10 %(V)	

© ZF Friedrichshafen AG

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 9

Lower explosion limit	Typical 1 %(V)	
Vapour pressure	< 0,5 Pa (20° C / 68° F)	Estimated value(s)
Relative vapour density	> 1	Estimated value(s)
Relative density	0,846 – 0,852 (15° C / 59° F)	
Density	846 – 852 kg/m³ (15° C / 59° F)	ISO 12185
Solubility(ies)		
Water solubility	negligible	
Solubility in other solvents	Data not available	
Partition coefficient: n- octanol/water	Pow: > 6	(based on infor- mation on similar products)
Auto-ignition temperature	> 320° C / 608° F	
Viscosity, dynamic	Data not available	
Viscosity, kinematic	5,4 – 5,8 mm²/s (100° C / 212° F)	DIN 51562-1
Explosive properties	Not classified	
Oxidizing properties	Data not available	

9.2 Other information

Conductivity:

This material is not expected to be a static accumulator.

Decomposition temperature:

Data not available

10. Stability and reactivity

© ZF Friedrichshafen AG

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



Trade name: ZF-LIFEGUARDFLUID 9

10.1	Reactivity	The product does not pose any further re- activity hazards in addition to those listed in the following subparagraph.
10.2	Chemical stability:	Stable.
10.3	Possibility of hazardous reactions:	Reacts with strong oxidising agents.
10.4	Conditions to avoid:	Extremes of temperature and direct sun- light
10.5	Incompatible materials:	Strong oxidising agents.
10.6	Hazardous decomposition products:	No decomposition if stored and applied as directed.

11. Toxicological information

11.1 Information on toxicological effects

Basis for assessment:	Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individ- ual component(s).
Information on likely routes of expo- sure	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity Product:	
Acute oral toxicity:	LD50 rat: > 5.000 mg/kg Remarks: Expected to be of low toxicity. Based on available data, the classification criteria are not met.
Acute inhalation toxicity:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity:	LD50 Rabbit: > 5.000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 9

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye. Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product: Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

Alkyl acetamide:

Remarks: Experimental data has shown that the concentration of potentially sensitising components present in this product does not induce skin sensitisation. May cause an allergic skin reaction in sensitive individuals.

Calcium alkaryl sulphonate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Germ cell mutagenicity

Product:

Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen. Based on available data, the classification criteria are not met.

- **IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- **ACGIH** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
- **OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



7F Aftermarket

Trade name: ZF-LIFEGUARDFLUID 9

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant. Does not impair fertility. Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product: Not considered an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible. Remarks: Slightly irritating to respiratory system.

12. Ecological information

12.1 Ecotoxicity

Basis for assessment:

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

Product:

Remarks: LL/EL/IL50 > 100 mg/l

© ZF Friedrichshafen AG

SAFETY DATA SHEET According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 9

	Toxicity to fish (Acute toxicity):	Practically non toxic: Based on available data, the classification criteria are not met.
	Toxicity to daphnia and other aquatic invertebrates (Acute toxicity):	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
	Toxicity to algae/aquatic plants (Acute toxicity):	Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic: Based on available data, the classification criteria are not met.
	Toxicity to fish (Chronic toxicity):	Remarks: Data not available
	Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity):	Remarks: Data not available
	Toxicity to microorganisms (Acute toxicity):	Remarks: Data not available
12.2	Persistence and degradability Product: Biodegradability	Remarks: Not readily biodegradable., Ma- jor constituents are inherently biodegrada- ble, but contains components that may persist in the environment.
12.3	Bioaccumulative potential Product: Bioakkumulation	Remarks: Contains components with the potential to bioaccumulate.
12.4	Mobility in soil Product: Mobility	Remarks: Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Remarks: Floats on water.
12.6	Other adverse effects Product: Additional ecological information	Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential. Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use. Poorly soluble mixture. Causes physical fouling of aquatic organisms.

© ZF Friedrichshafen AG Revision Date: 07.07.2018

15/20

Trade name: ZF-LIFEGUARDFLUID 9



13. Disposal considerations

13.1	Waste treatment methods Waste from residues:	Recover or recycle if possible. It is the responsibility of the waste genera- tor to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
		Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
	Contaminated packaging:	Dispose in accordance with prevailing reg- ulations, preferably to a recognized collec- tor or contractor. The competence of the collector or contractor should be estab- lished beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
	Local legislation Remarks	Disposal should be in accordance with applicable regional, national, and local laws and regulations.

14 Transport information

14.1 National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180) Not regulated as a dangerous good

14.2 International Regulation

IMDG-Code IATA-DGR Not regulated as a dangerous good Not regulated as a dangerous good

Remarks:

Special Precautions: Refer to Chapter 7,

© ZF Friedrichshafen AG



Trade name: ZF-LIFEGUARDFLUID 9

ZF Aftermarket

Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

14.3 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

15. Regulatory information

OSHA Hazards:

No OSHA Hazards

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Phosphoric acid	7664-38-2	5000	*
Normal Butyl Alcohol	71-36-3	5000	*
Normal Butyl Alcohol	71-36-3	100	*
Benzene	71-43-2	10	*
Naphthalene	91-20-3	100	*
Isobutyl alcohol	78-83-1	5000	*
Isobutyl alcohol	78-83-1	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

CERCLA Reportable Quantity

Calculated RQ exceeds reasonably attainable upper limit.

CERCLA Reportable Quantity

Calculated RQ exceeds reasonably attainable upper limit. Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA. The components with RQs are given for information.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	No SARA Hazards
SARA 302	No chemicals in this material are subject to the report- ing requirements of SARA Title III, Section 302.
SARA 313	This material does not contain any chemical compo- nents with known CAS numbers that exceed the

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



Trade name: ZF-LIFEGUARDFLUID 9

ZF Aftermarket

threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3: Naphthalene 91-20-3 0.0001 %

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9
Phosphoric acid	7664-38-2
Normal Butyl Alcohol	71-36-3
diphenylamine	122-39-4

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

The components of this product are reported in the following inventories:

	•	
EINECS/ELINCS/EC:	All components listed or polymer exempt.	
TSCA:	All components listed.	
DSL:	All components listed.	

16. Other information

www.zf.com/contact

Further information NFPA Rating (Health, Fire, Reactivity): 0, 1, 0

Abbreviations and Acronyms:	The standard abbreviations and acronyms used in this document can be looked up in reference litera- ture (e.g. scientific dictionaries) and/or websites. ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the Inter- national Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substanc- es ASTM = American Society for Testing and Materi- als BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service
ZF Friedrichshafen AG • ZF Aftermarket Obere Weiden 12, 97424 Schweinfurt, Germany Phone: +49 9721 4756-0	© ZF Friedrichshafen AG Revision Date: 07.07.2018

SAFETY DATA SHEET According to OSHA Hazard Communication Standard, 29 CFR 1910.1200





ZF Aftermarket

LL/EL/IL = Lethal Loading/Effective Load- ing/Inhibitory loading LL50 = Lethal Loading fifty MARPOL = International Convention for the Pre- vention of Pollution From Ships NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level OE_HPV = Occupational Exposure - High Produc- tion Volume PBT = Persistent, Bioaccumulative and Toxic PICCS = Philippine Inventory of Chemicals and Chemical Substances

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 9

Of Chemicals RID = Regulations Relating to International Carriage of Dangerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative

Further information

Training advice:

Other information:

Sources of key data used to compile the Safety Data Sheet:

Provide adequate information, instruction and training for operators.

A vertical bar () in the left margin indicates an amendment from the previous version.

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.