WOLF RACING
TRANS 75W-90 ESTER

25/09/2026
65521

This advanced full synthetic PAO based transmission oil with ester for racing vehicles has a very high viscosity index. The oil's excellent viscosity at low temperatures guarantees quick protection of all gears. It is blue colored.

APPLICATIONS

This is a special transmission oil with extreme pressure properties, specifically composed for use in extreme racing circumstances.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: long transmission life
Oil life durability: high level of thermal and oxidation stability

SPECIFICATIONS

API	GL-5
API	MT-1
ARVIN MERITOR	0-76-E
BMW	OSP
CHRYSLER	MS 9763
HEWLAND	SFU
HOLLINGER	SFU
LENCO TRANSMISSIONS	SFU
MACK	GO-J
MCLAREN	MOB PTX
PORSCHE	999.917.062.00
PORSCHE	999.917.067.00
PORSCHE	999.917.090.00
SADEV	SFU
SCHMIDT ANTRIEBSTECHNIK	SFU
X-TRAC	SFU
ZF	TE-ML 05A
ZF	TE-ML 05B
ZF	TE-ML 07A
ZF	TE-ML 12N
ZF	TE-ML 16F
ZF	TE-ML 17B
ZF	TE-ML 19C
ZF	TE-ML 21A

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.880
Kinematic viscosity at 40°C	ASTM D445	mm²/s	105
Kinematic viscosity at 100°C	ASTM D445	mm²/s	15.5
Viscosity index	ASTM D2270		156
Pour point	ASTM D6892	°C	-42
Colour	VISUAL		BLUE

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV