

WOLF OFFICIALTECH 10W40 UHPD S

11/08/2023
15706

This is a semi synthetic lubricant based on carefully selected very high quality base oils, which satisfies the highest performance standards for large trucks. It can be used for engines equipped with after treatment systems.

APPLICATIONS

Due to its versatile specification levels it is suitable for a wide range of commercial vehicles. Specifically recommended for large truck engines to satisfy the EURO VI standard, TIER IV interim, TIER IV final, TIER V , stage IIIB, stage IV, stage V.

FEATURES

Aftertreatment protection: full after treatment system protection

Total engine protection: outstanding engine cleanliness and durability

PERFORMANCE

ACEA	E6	LIEBHERR	LH-00-ENG5C LA
ACEA	E7	MACK	approval EO-S 4.5
ACEA	E9	MACK	EO-O Premium Plus
API	CJ-4	MAN	M3271-1
API	CK-4	MAN	M3477
API	SN	MAN	M3775
JASO	DH-2	MB	228.31
CATERPILLAR	ECF-2	MB	228.51
CATERPILLAR	ECF-3	MB	228.52
CUMMINS	CES 20081	MTU	Oil Category 2.1
CUMMINS	CES 20086	MTU	Oil Category 3.1
DETROIT DIESEL	DFS 93K218	RENAULT	approval RLD-3
DETROIT DIESEL	DFS 93K222	RENAULT	approval RLD-4
DEUTZ	DQC IV-10 LA	SCANIA	LA
DEUTZ	DQC-IV-18 LA	VOLVO	approval VDS-4.5
IVECO	18-1804 Classe TLS E9	VOLVO	VDS-4
JD	JDQ-78X		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.858
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	89.9
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.9
Viscosity index	ASTM D2270		158
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	10.2
Pour point	ASTM D6892	°C	-33
CCS viscosity at -25°C	ASTM D5293	mPa.s	6600
Flash Point COC	ASTM D92	°C	216

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

