

WOLF RACING TRANS 75W-140 ESTER

11/08/2023
65520

This is a full synthetic Extreme Pressure high performance gearbox and transaxle lubricant, enriched with ester, for racing vehicles offering an excellent anti-wear protection, a better resistance at high temperatures and a longer oil life time. It is blue colored.

APPLICATIONS

This lubricant can be used in gearboxes, transaxles and differentials with or without limited slip of racing vehicles.

FEATURES

Anti-wear protection: extended component life.
Extended oil life: excellent thermal and oxidation stability.

PERFORMANCE

API	GL-5	MB	235.61
API	GL-6	NISSAN	2189E
MIL	L-2105 B	ZF	TE-ML 05C
BMW	83221470080	ZF	TE-ML 12D
BMW	83222282583	ZF	TE-ML 16G
BMW	MSP/A	ZF	TE-ML 18
DREXLER	.	ZF	TE-ML 21C
GM	9986226		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.898
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	174
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	24.5
Viscosity index	ASTM D2270		173
Pour point	ASTM D6892	°C	-51
Colour	VISUAL		BLUE

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.