WOLF VITALTECH 15W40

06/10/2026
14636

This is a high-performance mineral diesel engine oil formulated to deliver reliable performance in a broad range of heavy-duty applications. It is suitable for low-emission engines (Euro II, Euro III and some Euro IV engines).

APPLICATIONS

Recommended for all modern diesel engines of trucks, off-road equipment and other heavy-duty applications. Universal use, including mixed fleets. Suitable for low-emission diesel engines with EGR (Euro II, III and some Euro IV). Meets and exceeds the demanding requirements of many U.S. and European diesel engine manufacturers.

FEATURES

Engine protection: high level of engine cleanliness and durability

SPECIFICATIONS

ACEA	A3/B4
ACEA	E7
API	CF-4
API	CG-4
API	CH-4
API	CI-4/SL
JASO	DH-1
ALLISON	C4
CATERPILLAR	ECF-1a
CATERPILLAR	ECF-2
CATERPILLAR	TO-2
CUMMINS	approval CES 20078
CUMMINS	CES 20076
CUMMINS	CES 20077
DETROIT DIESEL	DFS 93K215
DEUTZ	approval DQC-III-18
DEUTZ	DQC-III-10
DTFR	approval 15B110
GLOBAL	DHD-1
IVECO	18-1804 Classe T2 E7
MACK	approval EO-N
MACK	EO-L
MACK	EO-M PLUS
MAN	M3275-1
MB	228.3
MB	229.1
MTU	Oil Category 1
MTU	Oil Category 2
RENAULT	approval RLD-2
RENAULT	RLD
VOLVO	approval VDS-3
ZF	TE-ML 04C

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.8841
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	100.69
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	14.06
Viscosity index	ASTM D2270		142
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	11.9
Pour point	ASTM D6892	°C	-36
CCS viscosity at -20°C	ASTM D5293	mPa.s	6500
Sulfated Ash	ASTM D874	Mass %	1.49
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com