25/09/2026
3018

WOLF OFFICIALTECH
MULTI VEHICLE ATF HD-ND

This automatic transmission fluid is an high performance heavy duty synthetic transmission fluid. It is designed to deliver normal drain capabilities up to 60 000 km. It contains high quality synthetic base oils and an advanced additive technology. It is suitable for use in automatic transmission systems in both heavy duty trucks and buses.

APPLICATIONS

This automatic transmission fluid is designed for extended drain intervals for heavy duty trucks and buses as well as off-road equipment.

FEATURES

Frictional properties: smooth shift performance
Oil life durability: high level of thermal and oxidation stability
Anti-wear protection: long transmission life

SPECIFICATIONS

ALLISON	C4	VOITH	approval H55.6336xx
ALLISON	TES 295	VOITH	H55.6335xx
DTFR	13C170	VOLVO	STD 1273,40 (97340)
FORD	MERCON	VOLVO	STD 1273,41 (97341)
GM	DEXRON III-H	ZF	TE-ML 03D
MAN	339 L1	ZF	TE-ML 04D
MAN	339 V1/Z1	ZF	TE-ML 14A
MAN	339 V2/Z2	ZF	TE-ML 14B
MAN	339 Z11	ZF	TE-ML 14C
MAN	339 Z3	ZF	TE-ML 16L
MB	236.9	ZF	TE-ML 17C
MB	236.93	ZF	TE-ML 20B

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	42.0
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	8.4
Viscosity index	ASTM D2270		181
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	18000
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV