WOLF VITALTECH 10W40 ULTRA

25/09/2026
1227

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is a ultra high performance diesel (UHPD) engine oil that meets the highest performance standards for heavy trucks. This oil is not suitable for vehicles fitted with particulate filters.

APPLICATIONS

Recommended for turbocharged and naturally aspirated diesel engines. Perfectly suitable for new as well as older diesel vehicles.Exceeds the demanding requirements of most U.S. and European manufacturers.

FEATURES

Engine protection: high level of engine cleanliness and durability
Fuel economy: the purpose is great fuel economy and lower exhaust emissions
Cold start: very good fluidity at low temperature

SPECIFICATIONS

ACEA	E4
ACEA	E7
API	CF-4
API	CG-4
API	CH-4
API	CI-4/SL
JASO	DH-1
ALLISON	C4
CATERPILLAR	ECF-1a
CATERPILLAR	ECF-2
CATERPILLAR	TO-2
CUMMINS	CES 20076
CUMMINS	CES 20077
CUMMINS	CES 20078
DAF	EXTENDED DRAIN
DETROIT DIESEL	DFS 93K215
DEUTZ	DQC-III-10
DEUTZ	DQC-III-18
DTFR	13D100
DTFR	15B110
DTFR	approval 15B120
GLOBAL	DHD-1
IVECO	18-1804 Classe T2 E7
IVECO	18-1804 Classe T3 E4
MACK	approval EO-N
MACK	EO-M PLUS
MAN	approval M3277
MAN	M3275-1
MB	229.1
MTU	Oil Category 1
MTU	Oil Category 2
MTU	Oil Category 3
RENAULT	approval RLD-2
RENAULT	RLD
RENAULT	RXD
VOITH	Retarder Oil Class A
VOLVO	approval VDS-3

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.8566
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	85.34
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	13.77
Viscosity index	ASTM D2270		165
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	12.6
Pour point	ASTM D6892	°C	-39
CCS viscosity at -25°C	ASTM D5293	mPa.s	5000
Sulfated Ash	ASTM D874	Mass %	1.43
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com