# WOLF OFFICIALTECH
# 10W-30 IL HC

25/09/2026
16187

This semi-synthetic oil offers low wear, low emissions, and a strong fuel economy. Its carefully synthesized additive package targets soot and deposits to keep the engine clean.

## APPLICATIONS

This engine oil has been specifically developed to meet the challenging requirements of the latest ILSAC GF-7 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

## FEATURES

Cold start: high level of fluidity at low temperature
Fuel economy: great fuel economy and low exhaust emissions
Engine protection: ensures high level of the engine cleanliness

## SPECIFICATIONS

| | | | |
|---|---|---|---|
| API | approval SQ/RC | ILSAC | approval GF-7 A |
| API | SN Plus | ILSAC | GF-5 |
| API | SN/RC | ILSAC | GF-6 A |
| API | SP | CHRYSLER | MS 6395 |
| API | SP/RC | GM | 6094M |
| API | SQ | | |

## TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---|---|---|---|
| Density at 15°C | ASTM D4052 | g/ml | 0.849 |
| Kinematic viscosity at 40°C | ASTM D445 | mm²/s | 64.2 |
| Kinematic viscosity at 100°C | ASTM D445 | mm²/s | 10.6 |
| Viscosity index | ASTM D2270 | | 155 |
| B.N. (HCLO4 method) | ASTM D2896 | mg KOH/g | 7.4 |
| Pour point | ASTM D6892 | °C | -39 |
| Flash Point COC | ASTM D92 | °C | 220 |

**We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.**

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com



The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV