WOLF OFFICIALTECH
ATF 9G

25/09/2026
3017

This a is synthetic automatic transmission fluid with a special selection of top quality base oils and a specific additive package to ensure the smooth functioning of automatic transmissions of Mercedes-Benz. It is an ATF of the newest generation developed for 9-gear automatic transmissions of Mercedes-Benz vehicles. It guarantees an excellent wear protection in every operating situation.

APPLICATIONS

This ATF is developed for use in the newest 9G-Tronic automatic transmission of the Series W9A 700 by Mercedes-Benz, also known as NAG3 (New Automatic Transmission of the 3rd Generation). It should be used in MB automatic transmissions requiring the specification MB 236.17. It is backward compatible with the former MB 236.16.

FEATURES

Stability: good mechanical stability
Temperature stability: high thermal and oxidative stability
Wear protection: high level of protection against wear

SPECIFICATIONS

MB	236.17

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Color	ASTM D1500		YELLOW / GOLD
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 100°C	ASTM D445	mm²/s	5.0
Viscosity index	ASTM D2270		162
Pour point	ASTM D6892	°C	-45
Flash Point COC	ASTM D92	°C	237
Kinematic viscosity at 40°C	ASTM D445	mm²/s	21

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV