

WOLF OFFICIALTECH 10W40 CP

10/10/2023
33127

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This oil is an advanced engine oil, especially developed to meet ACEA A3/B4 requirements and to fulfill Euro 4 norms. It is designed for the lubrication of four-stroke gasoline and diesel cars, including diesel engines with direct injection such as Common Rail, HDI, CDI, etc. Key features include a low ash formulation and a high resistance to ageing.

APPLICATIONS

Ideal for most gasoline and diesel engines - normally aspirated and supercharged. Particularly recommended for Direct Injection diesel engines - Common Rail, HDI, CDI, etc. Can be used all year round - thanks to its optimum viscosity index.

FEATURES

Total engine protection: performance in keeping the engine clean.

Outstanding thermal and oxidative stability: superior viscosity stability

Superb shear stability performance: optimal contribution to high temperature viscosity

PERFORMANCE

ACEA	A3/B3-16	MB	229.1
ACEA	A3/B4	MB	approval 229.3
API	approval SN	PSA	B71 2300-2022
API	CF	RENAULT	RN 0700
FIAT	9.55535-D2	RENAULT	RN 0710
FIAT	9.55535-G2	VW	approval 501 01
LADA	LADA-AVTOVAZ	VW	approval 505 00
MB	226.5		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.859
Kinematic viscosity at 40°C	ASTM D445	mm²/s	91.0
Kinematic viscosity at 100°C	ASTM D445	mm²/s	14.2
Viscosity index	ASTM D2270		161
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	10.4
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	1.3
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

