

WOLF OFFICIALTECH MULTI VEHICLE ATF HD-ND

04/09/2023
3018

This automatic transmission fluid is an high performance heavy duty synthetic transmission fluid. It is designed to deliver normal drain capabilities up to 60 000 km. It contains high quality synthetic base oils and an advanced additive technology. It is suitable for use in automatic transmission systems in both heavy duty trucks and buses.

APPLICATIONS

This automatic transmission fluid is designed for extended drain intervals for heavy duty trucks and buses as well as off-road equipment.

FEATURES

Frictional properties: smooth shift performance.

Extended oil life: excellent thermal and oxidation stability.

Anti-wear protection: extended transmission life.

PERFORMANCE

ALLISON	C4	VOLVO	STD 1273,41 (97341)
ALLISON	TES 295	ZF	TE-ML 03D
DAIMLER TRUCK	DTFR 13C170	ZF	TE-ML 04D
FORD	MERCON	ZF	TE-ML 14A
GM	DEXRON III-H	ZF	TE-ML 14B
MAN	339 V2/Z2	ZF	TE-ML 14C
MAN	339 Z11	ZF	TE-ML 16L
MB	236.9	ZF	TE-ML 17C
VOITH	H55.6336xx	ZF	TE-ML 20B
VOLVO	STD 1273,40 (97340)		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	42.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.4
Viscosity index	ASTM D2270		181
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	18000
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

