WOLF VITALTECH
75W-80 MV PREMIUM

25/09/2026
2219

This is a high quality semi synthetic transmission oil, suitable for nearly all manual gearboxes of passenger cars. It is especially suitable as a replacement for specific OEM original oils and reduces the complexity and storage of gearbox oils. Tested under strict conditions, this oil satisfies the general performance requirements of most car makers and models.

APPLICATIONS

This oil is recommended for all hypoid transmissions and is also suitable for spiral bevel gears, worm wheels and most transaxles in all weather.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: long transmission life
Oil life durability: good resistance to oil degradation

SPECIFICATIONS

API	GL-4 +	GM	1940768
ALFA ROMEO	SFU	GM	1940776
BMW	23001434404	GM	88861800
BMW	23007533513/818	GM	88861801
BMW	83 22 2 339 219	GM	93165290
BMW	83 22 0 140 516	HONDA	08261-99964
BMW	83220309031	HONDA	08798-9031
BMW	83220403247	HONDA	MTF 94
BMW	83227533818	HONDA	MTF-7289
BMW	MTF LT-1	HONDA	Special HONDA MTF
BMW	MTF LT-2	HONDA	Special HONDA MTF-II
BMW	MTF LT-3	HYUNDAI	02200-00130 TOD
BMW	MTF LT-4	LANCIA	SFU
BMW	MTF LT-5	LAND ROVER	STC 9157
FIAT	14621616	LAND ROVER	STC 9158
FIAT	9.55550,CTR F178.B06	LAND ROVER	TYK500030
FIAT	9.55550,CTR F921.B10	MB	235.10
FIAT	9.55550-MX3	MITSUBISHI	MZ312644
FIAT	9.55550-MZ1	NISSAN	999MP-MTF20P
FIAT	9.55550-MZ10	NISSAN	KE91699932R
FORD	1382914	NISSAN	MT-XZ
FORD	1547953	NISSAN	MT-XZ TL (JR Type)
FORD	ESD-M2C186-A	OPEL	GM 1940182
FORD	WSD-M2C200-D	OPEL	GM 1940757
FORD	WSS-M2C200-C/C2/C3	OPEL	GM 1940768
FORD	WSS-M2C200-D2	OPEL	GM 1940776
GM	1940711	PSA	9730 A2
GM	1940757	PSA	9730 A8

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

PSA	B71 2315	VW	G 009 317
PSA	B71 2330	VW	G 052 171
SUBARU	K0321-F0090	VW	G 052 178
TOYOTA	08885-00705	VW	G 052 512
TOYOTA	JWS 227	VW	G 052 527
VOLVO	1161681	VW	G 052 532
VOLVO	1161745	VW	G 052 726
VOLVO	97308	VW	G 052 911
VOLVO	97309	VW	G 055 532
VOLVO	97310	VW	G 055 538
VW	501 50	VW	G 50
VW	AMAROK 0C6	VW	TL 52 532
VW	G 005 000	VW	TL 726

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.867
Kinematic viscosity at 40°C	ASTM D445	mm²/s	48.2
Kinematic viscosity at 100°C	ASTM D445	mm²/s	8.8
Viscosity index	ASTM D2270		164
Pour point	ASTM D6892	°C	-39
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	100000
Flash Point COC	ASTM D92	°C	212

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com