25/09/2026
65524

WOLF RACING
TRANS/AXLE LS 75W-140 ESTER

This is a sustainable RRBO high performance gearbox and transaxle lubricant, enriched with ester and PAO, for racing vehicles offering an excellent anti-wear and EP protection, a better resistance at high temperatures and a longer oil life time.

APPLICATIONS

This sustainable RRBO lubricant can be used in gearboxes, transaxles and differentials with or without limited slip of racing vehicles.

FEATURES

Anti-wear protection: long component life
Oil life durability: high level of thermal and oxidation stability

SPECIFICATIONS

API	GL-5	GM	9986226
API	GL-6	GM	9986290
API	MT-1	HEWLAND	SFU
DUTCHMAN AXLES	SFU	HOLLINGER	SFU
MIL	L-2105 B	MACK	GO-J
MIL	L-2105 C	MB	235.61
MIL	L-2105 D	M-SPORT	Rally3/Rally4/Rally5/R1/R2/R3
MIL	L-2105 E	NISSAN	2189E
SAE	J 2360	RICARDO	SFU
ARVIN MERITOR	0-76-N	SADEV	SFU
ASTON MARTIN	6G33-7106-AA/S	SALISBURY	SFU
BMW	83 22 1 470 080	SCANIA	STO 1:0
BMW	83 22 2 282 583	SCANIA	STO 2:0A
BMW	83 22 9 407 803	VW	G 052 539
BMW	83 22 9 407 870	X-TRAC	SFU
BMW	MSP/A	ZF	TE-ML 05A
CHRYSLER	68218658AA	ZF	TE-ML 05B
CHRYSLER	MS 8985	ZF	TE-ML 05C
DANA	SFU	ZF	TE-ML 05D
DREXLER	SFU	ZF	TE-ML 07A
FERRARI	PAKELO GLOBAL MULTIGEAR DLS	ZF	TE-ML 12D
FORD	ESW-M2C104-A	ZF	TE-ML 12N
FORD	ESW-M2C119-A	ZF	TE-ML 16F
FORD	WSL-M2C192-A + EST-M2C118-A	ZF	TE-ML 16G
FORD	WSS-M2C187-A	ZF	TE-ML 19C
GM	12346140	ZF	TE-ML 21A
GM	1942386	ZF	TE-ML 21C

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.898
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	179
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	24.3
Viscosity index	ASTM D2270		167
Pour point	ASTM D6892	°C	-51
Colour	VISUAL		LIGHT BROWN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV