WOLF OFFICIALTECH
5W30 C3

25/09/2026
65607

This is a full synthetic lubricant based on carefully selected very high quality base oils, formulated using the latest technology for Mid SAPS catalyst compatible engine oils. Its special formulation combines fuel economy with an extended service life. The reduced ash formulation protects particulate filters and exhaust after-treatment devices.

APPLICATIONS

This dexos 2TM approved oil is required for all new GM/Opel/Vauxhall/Chevrolet diesel and gasoline models. GM/Opel has advised that the dexos 2TM specification is backward compatible to older GM/Opel specifications (GM-LL-A-025 and GM-B-LL-025). The majority of GM/Opel/Vauxhall/Chevrolet diesel and gasoline vehicles can use dexos 2TM lubricants. C2* meets all engine protection requirements of ACEA C2.

FEATURES

Aftertreatment protection: the purpose is full aftertreatment device protection
Engine protection: high level of engine cleanliness and durability
Fuel economy: the purpose is great fuel economy and lower exhaust emissions

SPECIFICATIONS

ACEA	C2
ACEA	C3
API	approval SN
API	CF
API	SP
BMW	LONGLIFE-04
CHRYSLER	MS 11106
FIAT	9.55535-S3
FORD	WSS-M2C917-A
GM	approval dexos™2
GM	dexos™1 Gen 3
GM	dexos™D
HYUNDAI	SFU
KIA	SFU
MB	229.31
MB	229.51
MB	229.52
OPEL	GM-LL-A-025
OPEL	GM-LL-B-025
OPEL	OV 040 1547 - D30
OPEL	OV 040 1547 - G30
VW	502 00 < 2017
VW	505 00
VW	505 01

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	67.1
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	12.2
Viscosity index	ASTM D2270		182
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	8.0
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	5400
Sulfated Ash	ASTM D874	Mass %	0.77
Flash Point COC	ASTM D92	°C	234

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com