



## **XK1 SYNTHETIC PLUS TECHNOLOGY ENGINE OIL**

### **SAE 5W-30 (SL/CF – A5/B5) - ADVANCE**

#### DESCRIPTION:

Latest generation semi-synthetic lubricant. Specifically for high performance multi-valve and/or turbocharged petrol engines and supercharged diesel engines with DPF. **Specific lubricant for FORD engines.**

#### FEATURES:

Thanks to its innovative formula, **XK1 Synthetic Plus Technology Engine Oil SAE 5W-30 ADVANCE** guarantees:

- excellent lubrication when cold, under all operating conditions, even at extremely low outside temperatures;
- low viscosity when cold for reduced fuel consumption;
- low evaporation for reduced oil consumption;
- excellent detergent and dispersant power for a cleaner engine.

#### CONFORMITY:

INTERNATIONAL SPECIFICATIONS	
ACEA	A5/B5
API	SL/CF

CONFORMS TO THE FOLLOWING PERFORMANCE REQUIREMENTS	
FORD	WSS-M2C913-D
JAGUAR / LAND ROVER	STJLR.03.5003
RENAULT	RN0700

#### SPECIFICATIONS:

TYPICAL FEATURES			
Features	Method	Typical values	Unit of measure
Density at 20°C	ASTM-D4052	0,847	g/cm <sup>3</sup>
Viscosity at 40°C	ASTM-D7279	63,0	cSt
Viscosity at 100°C	ASTM-D7279	11,1	cSt
Viscosity at -30°C	ASTM-D5293	4230	cP
Viscosity index	ASTM-D2270	169	-
Flash point	ASTM-D92	225	°C
Sliding point	ASTM-D5950	-36	°C

#### NOTES:

*The above data are not a specification and are subject to standard production tolerance values. Considering the multiple possible applications and the possible interference by elements in no way related to us, we cannot be held in any way liable for results and experimental tests carried out at the sole risk of the user.*