WOLF OFFICIALTECH
5W40 C3

25/09/2026
65630

This synthetic engine oil is developed to suit the needs of some of the highest performing petrol engines. Thanks to its highly durable formula, this lubricant offers improved fuel economy and complete engine protection within even the most demanding engine designs. It is suitable for hybrid cars when the OEM specifications are met.

APPLICATIONS

This engine oil enhances the performance of several W12, V10 and V8 engines of several manufacturers. Its top quality properties are proven by the VW 511 00 and Porsche C40 specifications, which broadens the lubricant's applicability to a range of Audi, Bentley and Lamborghini cars.

FEATURES

Fuel economy: the purpose is great fuel economy and lower exhaust emissions
Aftertreatment protection: the purpose is full aftertreatment device protection
Engine protection: high level of engine cleanliness and durability

SPECIFICATIONS

ACEA	C3	LADA	SFU
API	CF	LANCIA	SFU
API	SN	LANDWIND	SFU
ABARTH	SFU	LIFAN	SFU
ALFA ROMEO	SFU	MASERATI	SFU
BMW	LONGLIFE-04	MB	226.5
BYD	SFU	MB	229.31
CADILLAC	SFU	MB	229.51
CHEVROLET	SFU	MB	229.52
CHRYSLER	SFU	MINI	SFU
DACIA	SFU	MITSUBISHI	SFU
DODGE	SFU	MORGAN	SFU
FERRARI	SFU	OPEL	OV 040 1547 - D40
FIAT	9.55535-GH2	OPEL	SFU
FIAT	9.55535-S2	PIAGGIO	SFU
FIAT	SFU	PORSCHE	approval C40
FORD	SFU	RENAULT	RN 0700
FORD	WSS-M2C917-A	RENAULT	RN 0710
FREIGHTLINER	SFU	ROLLS-ROYCE	SFU
GAZ	SFU	SAAB	SFU
GM	dexos™2	SAMSUNG	SFU
GREAT WALL	SFU	SEAT	SFU
HONDA	SFU	SKODA	SFU
HYUNDAI	SFU	SMART	SFU
INFINITI	SFU	SSANG YONG	SFU
ISUZU	SFU	SUZUKI	SFU
KIA	SFU	TOYOTA	SFU

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

VW	505 00	VW	511 00
VW	505 01		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	73.0
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	13.5
Viscosity index	ASTM D2270		191
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	7.8
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	0.79
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV