# WOLF OFFICIALTECH
# 0W-30 MS-S-DH1

25/09/2026
65667

A mid SAPS synthetic based engine oil focused on the Stellantis engine oil specification FPW9.55535/DH1.

## APPLICATIONS

This synthetic based engine oil is specifically designed for 2.2 liter diesel engines used in all European Stellantis light commercial vehicles (LCV's) which require an engine oil according to the stringent Stellantis FPW9.55535/DH1 specification.
(Fiat Euro 6.4 Multijet B2.2 diesel engines, used in Boxer, Ducato, Jumper, and Movano. For engine types E6F, F6F, G6F, G6H, G8F.)

## FEATURES

Cold start: high level of fluidity at low temperature
Fuel economy: the purpose is good fuel economy and low exhaust emissions
Engine protection: ensures high level of the engine cleanliness

## SPECIFICATIONS

| | |
|---|---|
| STELLANTIS | FPW9.55535/DH1 |

## TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---|---|---|---|
| Density at 15°C | ASTM D4052 | g/ml | 0.843 |
| Kinematic viscosity at 40°C | ASTM D445 | mm²/s | 53.3 |
| Kinematic viscosity at 100°C | ASTM D445 | mm²/s | 9.64 |
| Viscosity index | ASTM D2270 | | 168 |
| Pour point | ASTM D6892 | °C | -51 |
| Flash Point COC | ASTM D92 | °C | 225 |

**We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.**

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com