WOLF OFFICIALTECH
5W30 C4

25/09/2026
65608

This is a full synthetic lubricant based on carefully selected very high quality base oils, specifically formulated to provide superior protection of the after-treatment systems of Renault engines.

APPLICATIONS

Gasoline and diesel engines of passenger cars with or without turbo which are equipped with a DPF and a TWC (Three-Way Catalyst).

FEATURES

Aftertreatment protection: the purpose is full aftertreatment system protection
Engine protection: high level of engine cleanliness and durability
Fuel economy: the purpose is great fuel economy and lower exhaust emissions

SPECIFICATIONS

ACEA	C3	MB	approval 226.51
ACEA	C4	MB	approval 229.51
FIAT	9.55535-S4	RENAULT	approval RN 0720
MB	229.31	SUZUKI	SFU

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm²/s	67.1
Kinematic viscosity at 100°C	ASTM D445	mm²/s	11.8
Viscosity index	ASTM D2270		173
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	6.4
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	5800
Sulfated Ash	ASTM D874	Mass %	0.5
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV