WOLF VITALTECH 10W-60 M

25/09/2026
16128

This is a full synthetic lubricant based on carefully selected very high quality base oils of the latest generation, for the lubrication of all gasoline and diesel engines with turbo.

APPLICATIONS

4 stroke gasoline engines, multi-valves, turbo.4 stroke diesel engines, with or without turbo.

FEATURES

Cold start: very good fluidity at low temperature
Engine protection: high level of engine cleanliness and durability

SPECIFICATIONS

ACEA	A3/B4	MB	229.3 Level
API	SN/CF	VW	501 01
BMW	LONGLIFE-01 Level	VW	505 00
BMW	M-MODELS		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm²/s	156
Kinematic viscosity at 100°C	ASTM D445	mm²/s	25.0
Viscosity index	ASTM D2270		194
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	9.5
Pour point	ASTM D6892	°C	-36
CCS viscosity at -25°C	ASTM D5293	mPa.s	3800
Sulfated Ash	ASTM D874	Mass %	1.0
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV