WOLF OFFICIALTECH
MULTI VEHICLE ATF HD-LD

25/09/2026
3015

This transmission fluid is an ultra high performance heavy duty synthetic transmission fluid. It is designed to deliver significantly extended drain capabilities. It contains superior quality synthetic base oils and advanced additive technologies and is suitable for use in automatic transmission systems in both heavy duty trucks and buses.

APPLICATIONS

This transmission fluid is designed for extended drain in heavy duty automatic truck and bus as well as off-road equipment transmissions.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: long transmission life
Oil life durability: high level of thermal and oxidation stability

SPECIFICATIONS

ALLISON	TES 295	ZF	approval TE-ML 20C
ALLISON	TES 389	ZF	approval TE-ML 25C
DTFR	13C140	ZF	TE-ML 03D
DTFR	13C150		
DTFR	13C170		
EvoBus	27.000-017		
FORD	WSS-M2C195-A		
GM	DEXRON III-G		
GM	DEXRON III-H		
MAN	339 V1		
MAN	339 V2		
MAN	approval 339 Z12		
MAN	approval 339 Z3/V3		
MB	236.6		
MB	236.7		
MB	236.8		
MB	236.9		
VOITH	approval 150.014524.xx		
VOITH	H55.6335xx		
VOITH	H55.6336xx		
VOLVO	STD 1273,39 (97339)		
VOLVO	STD 1273,40 (97340)		
VOLVO	STD 1273,41 (97341)		
VOLVO	STD 1273,42 (97342)		
ZF	approval TE-ML 04D		
ZF	approval TE-ML 14C		
ZF	approval TE-ML 16M		
ZF	approval TE-ML 16S		

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.842
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	36.9
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	7.08
Viscosity index	ASTM D2270		157
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	13000
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV