

WOLF OFFICIALTECH 75W140 LS GL 5

11/08/2023
2307

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is a high performance transmission oil for all differentials, including those equipped with a "limited slip" mechanism. It is characterized by an exceptionally high viscosity stability at different temperatures and a very high fluidity at low temperature.

APPLICATIONS

This product is used in highly loaded axles and reduction gears of cars, trucks and off-road equipment. It has "limited-slip" characteristics, and is specifically recommended for 4X4 vehicles.

FEATURES

Frictional properties: very smooth gear shifting, no vibration

Anti-wear protection: extended transmission life

Extended oil life: excellent thermal and oxidation stability

PERFORMANCE

API	GL-5	FORD	WSS-M2C187-A
MIL	L-2105 C	FORD	WSS-M2C192-A
MIL	L-2105 D	FORD	WSS-M2C192A+/M2C118-A
BMW	83 22 1 470 080	GM	12346140
BMW	83 22 2 282 583	GM	1942386
BMW	MSP/A		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.893
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	170
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	26.5
Viscosity index	ASTM D2270		195
Pour point	ASTM D6892	°C	-51
Flash Point COC	ASTM D92	°C	190

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

