# WOLF RACING
# TRANS/AXLE 75W-90 ESTER

25/09/2026
65525

This advanced sustainable RRBO transmission oil, fortified with ester and PAO, is especially developed for racing vehicles.
The oil's excellent viscosity at low temperatures guarantees quick protection of all gears.

## APPLICATIONS

This is a special sustainable RRBO transmission oil with extreme pressure properties, specifically composed for use in extreme racing circumstances.

## FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: long transmission life
Oil life durability: high level of thermal and oxidation stability

## SPECIFICATIONS

| | |
|---|---|
| API | GL-5 |
| API | MT-1 |
| ARVIN MERITOR | 0-76-E |
| BMW | 83 22 2 365 987 |
| BMW | OSP |
| CHRYSLER | MS 9763 |
| DANA | SFU |
| FIAT | 9.55550-DA3 |
| FIAT | 9.55550-DA4 |
| FIAT | 9.55550-DA6 |
| FIAT | 9.55550-DA7 |
| FIAT | 9.55550-DA8 |
| FIAT | 9.55550-MX4 |
| HEWLAND | SFU |
| HOLLINGER | SFU |
| LENCO TRANSMISSIONS | SFU |
| MACK | GO-J |
| MCLAREN | MOB PTX |
| PORSCHE | 000.043.204.19 |
| PORSCHE | 000.043.204.20 |
| PORSCHE | 000.043.204.71 |
| PORSCHE | 000.043.207.76 |
| PORSCHE | 000.043.210.12 |
| PORSCHE | 000.043.304.71 |
| PORSCHE | 000.043.305.55 |
| PORSCHE | 999.917.062.00 |
| PORSCHE | 999.917.067.00 |
| PORSCHE | 999.917.090.00 |
| PORSCHE | 999.917.545.00 |
| PORSCHE | 999.917.546.00 |
| RICARDO | SFU |
| SADEV | SFU |
| SCANIA | STO 2:0A FS |
| SCHMIDT ANTRIEBSTECHNIK | SFU |
| X-TRAC | SFU |
| ZF | TE-ML 05A |
| ZF | TE-ML 05B |
| ZF | TE-ML 07A |
| ZF | TE-ML 12N |
| ZF | TE-ML 16F |
| ZF | TE-ML 17B |
| ZF | TE-ML 19C |
| ZF | TE-ML 21A |

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com



The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

## TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---|---|---|---|
| Density at 15°C | ASTM D4052 | g/ml | 0.881 |
| Kinematic viscosity at 40°C | ASTM D445 | $mm^2/s$ | 104 |
| Kinematic viscosity at 100°C | ASTM D445 | $mm^2/s$ | 15.4 |
| Viscosity index | ASTM D2270 | | 156 |
| Pour point | ASTM D6892 | °C | -42 |
| Colour | VISUAL | | LIGHT BROWN |

**We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.**

**WOLF OIL CORPORATION NV**
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com



The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV